



TYPHOON MANUAL

Universe House, Key Industrial Park, Willenhall, West Midlands,
WV13 3YA, England
Tel: +44 (0) 1902 722144 Fax: +44 (0) 1902 722880
E-mail: Sales@webley.co.uk
www.webley.co.uk www.logun.com www.webleyandscott.co.uk
www.airgunsport.com

Universe House, Key Industrial Park, Willenhall, West Midlands,
WV13 3YA, England
Tel: +44 (0) 1902 722144 Fax: +44 (0) 1902 722880
E-mail: Sales@webley.co.uk
www.webley.co.uk www.logun.com www.webleyandscott.co.uk
www.airgunsport.com

Manual for the Typhoon pistol

Specification

The Typhoon is a spring operated, semi recoiless, break action air pistol fitted with a precision-rifled barrel primarily suited to waisted lead pellets.

The gun is available in either .177 (4.5mm) or .22 (5.5mm) calibre. As with all rifled barrels, darts may be used but some deterioration of the rifling will occur.

The gun incorporates many additional features which include:

1. An adjustable trigger.
2. A manual safety catch (i.e. selective use)
3. A rearsight vertical and horizontal adjustment.
4. Anti bear trap cockings action

General Instructions

Typhoon air pistols are supplied fully assembled and are ready for immediate use once familiarisation of the pistol and an appreciation of the basic safety rules have been completed.

The Basic safety rules

1. Treat every pistol as if it is loaded.
2. Never point a pistol at ANYONE, or allow anyone to point a pistol at you even if you think it is not loaded.
3. Always carry the pistol so that the direction of the muzzle is under control, even if you stumble.
4. Always be sure of your target and what lies behind it, before you squeeze the trigger.
5. Never leave a loaded pistol unattended.
6. Beware of targets which tend to cause ricochets.

To Load The Typhoon is fitted with a manual **SAFETY CATCH** which may be applied before or after the pistol is cocked.

The **SAFETY** is engaged by pushing the lever so that the **RED LINE IS NOT VISIBLE**



To cock the pistol:

1. Rap the muzzle of the barrel (by the retracting foresight) so that the action opens .



2. Rotate the barrel fully downwards compressing the spring



3. Insert the pellet into the exposed breech of the barrel.



4. Rotate the barrel back to the locked position.
5. When you are ready, **DISENGAGE** the **SAFETY** by pushing the lever so the **RED LINE IS VISIBLE**, take aim and squeeze the trigger smoothly. Be sure there is an adequate backstop behind the target.